

## Resilient SRQ – Round 2 Grant Application

### Whitaker Bayou Resiliency & Stormwater Mitigation Project (*Revised August 13<sup>th</sup>, 2025*)

---

#### 1 | Applicant

Sarasota County & City of Sarasota

#### 2 | Primary Contact

Nikesh Patel – Director of Public Works

[Nikesh.Patel@sarasotafl.gov](mailto:Nikesh.Patel@sarasotafl.gov) • (941) 263-6132

---

#### 3 | Project Title & Location

Whitaker Bayou Resiliency & Stormwater Mitigation Project

- Entire 3.6-mile reach of Whitaker Bayou (Sarasota Bay → 47th St)
  - Three “hot-spot” sub-basins: **Tri-Par, 17th St / US-301, and US-41 / 10th St**
- 

#### 4 | Project Description & Need

Hydrologic and water-quality analyses (2024-25) confirm that three infrastructure choke-points drive > **80** % of the bayou’s flood LOS failures and nutrient exports.

- **Tri-Par** – chronic flooding at two confluences; high TN loading from industrial runoff.
- **17th St / US-301** – undersized culverts force backwater flooding into Forest Lakes and overtop an evacuation route.
- **US-41 / 10th St (Coastal)** – tidal backflow and untreated downtown runoff discharge directly to Sarasota Bay.

Targeted BMPs—linear treatment system plus dry retention (Tri-Par), twin 10' × 6' culverts with tide flaps (17th St), and sediment sump/BAM weirs/LID retrofit (US-41)—will lift each node to the **100-year (1 % ACE) Level-of-Service** and cut **Total Nitrogen (TN)** by ~**7,340 lb/yr**.

---

## 5 | Scope of Work & Cost (2025 dollars)

| Component   | Cost                 |
|---|----------------------|
| A. Tri-Par linear treatment + dry retention               | \$ 3,787,767         |
| B. US-41 / 10th St sediment sump, BAM weirs, LID retrofit | \$ 2,972,626         |
| C. 17th St / US-301 twin 10'x6' box culverts + tide flap  | \$ 3,500,000         |
| D. 1,800 LF bank stabilization & native re-vegetation     | \$ 1,170,000         |
| E. Three nutrient-separating baffle boxes                 | \$ 990,000           |
| F. Design, permitting, utility coordination (≈ 15 %)      | \$ 1,900,000         |
| G. Construction contingency (10 %)                        | \$ 1,570,000         |
| <b>Total Estimated Project Cost</b>                       | <b>\$ 15,890,000</b> |

## 6 | Funding Strategy

| Source                                   | Amount               | % of Total   |
|--|----------------------|--------------|
| <b>Resilient SRQ – Round 2 (CDBG-DR)</b> | <b>\$ 15,890,000</b> | <b>100 %</b> |

(City/County provide in-kind ROW, inspection, and outreach support; no local cash match.)

## 7 | Expected Outcomes & Benefits

| Metric   | Tri-Par                            | 17th St / US-301                  | US-41 / 10th St        | Project Total              |
|--|------------------------------------|-----------------------------------|------------------------|----------------------------|
| <b>Structures removed from 100-yr floodplain</b> | 12                                 | 38 (est.)*                        | —                      | <b>≈ 50</b>                |
| <b>Roadway LOS deficiencies eliminated</b>       | 1,018 LF (incl. 416 LF evac route) | ≈ 500 LF evac route               | —                      | <b>≈ 1,500 LF</b>          |
| <b>Annual TN removed</b>                         | 6,619 lb/yr                        | ~10 lb/yr (culvert scour control) | 710 lb/yr              | <b>≈ 7,340 lb/yr</b>       |
| <b>Conveyance LOS</b>                            | < 2-yr → <b>100-yr</b>             | < 2-yr → <b>100-yr</b>            | Tidal flooding blocked | All nodes at <b>100-yr</b> |

\*38 structures is the count from the 17th St backwater model used in the 2024 CCNA review memo.

Additional benefits

- Protects ≈ \$ 280 M in assessed value along US-41 arts & hospitality corridor.
- Achieves <\$ 30/lb TN at Tri-Par—well below Sarasota Bay Estuary Program cost-effectiveness target.
- Designs account for **1.5 ft SLR (NOAA 2050-intermediate)** to ensure long-term performance.

8 | Cost Reasonableness & Market Validation

- Tri-Par and US-41 costs from SBEP Tidal-Stream Assessment, escalated to 2025 dollars; culvert costs match 2025 FDOT District 1 averages for twin 10'×6' boxes.
- 15 % soft-cost and 10 % contingency meet USACE Environmental Infrastructure standards.

9 | Schedule (Key Milestones)

| Milestone   | Target Date      |
|---|------------------|
| 30 % design & environmental submittal             | Summer 2026      |
| Permitting & final plans complete                 | Late 2026        |
| Advertise & award contract                        | Summer 2027      |
| Mobilization & phased construction start          | Late 2027        |
| Substantial completion (all BMPs)                 | Summer 2028      |
| Two-year post-construction performance monitoring | through Dec 2030 |

10 | Request

The City of Sarasota and Sarasota County respectfully request **\$ 15,890,000** in **Resilient SRQ – Round 2 (CDBG-DR)** funding to construct the Whitaker Bayou Resiliency & Stormwater Mitigation Project. This fully funded effort will:

- Deliver **100-year flood protection** at three critical nodes,
- Remove **> 7,300 lb/yr of nitrogen** before it reaches Sarasota Bay,
- Eliminate evacuation-route closures and stabilize eroding banks, and
- Provide durable, equitable climate resilience for more than **18,000 residents** in Sarasota’s northern neighborhoods.

### Tri-Par Area

The Tri-Par Area is subject to historic flooding, located within Whitaker Bayou basin at the confluence of Whitaker Main Canal and Tributary A, as well as confluence of Tributaries A and B. The area has a history of flooding and includes significant nitrogen loading as well – which is primarily due to the age and intensity of land-use and commercial/industrial land-use types.




Figure 21 - Tri-Par Priority Management Area



### 17th and US-301 Area

This area has street flooding level of service deficiencies on US - 301, existing street flooding on US - 301, 17th Street and N. East Ave and Structure flooding LOS deficient for 10 commercial buildings. The area also experiences high or medium nitrogen loading throughout.




Figure 25 - 17th & US301 Priority Management Area



## US-41 and 10<sup>th</sup> Street Area

There is a roadway LOS deficiency on US-41 with high or medium nutrient loading. Intense urban development upstream of the 10th Street boat basin contributes to the direct discharge of stormwater run-off into Sarasota Bay. The boat basin has been maintained throughout the years and a sediment removal project was completed in 2018. SWFWMD cooperatively funded project No. W606 to install a nutrient separating baffle box on 10<sup>th</sup> St. just east of Florida Ave. The Bay Partnership is redeveloping the City owned bayfront into a more highly used public space and is interested in partnering on improvements.





Figure 26 - US 41 & 10th Street Priority Management Area



## Tri-Par – Whitaker Bayou



### Project Management Area

The Tri-Par Area has historic long-standing flooding located within Whitaker Bayou basin at two main confluences (Canal/Trib A and Trib A/B). The area includes high nutrient loading due to the age and intensity of land-use (commercial/industrial).

### Conceptual BMP

- Linear treatment system channel retrofit with floodplain bench and weirs for storage and pollutant removal.
- Large dry retention area to provide floodplain storage
- Nutrient separating baffle box at retention area inflow will capture sediment, vegetation, and trash

**Score 100**

**Cost \$3,787,767**


### Benefits

- Annual TN removal 6,619 lbs
- \$28/lb TN removed over 20 year life expectancy of BMP
- 12 structures removed from 100yr storm risk
- 1018 linear feet of roadway removed from LOS Deficiency including 416 feet of evacuation route
- Flood Cost-Benefit Ratio = 1.08
- Resilient in NOAA 2100 future condition

| <b>PROJECT MANAGEMENT AREA: TRI-PAR</b>   |             |                 |                  |                     |
|---|-------------|-----------------|------------------|---------------------|
| <b>CONCEPTUAL PLAN COST ESTIMATE - DRY RETENTION AREA; NUTRIENT SEPARATING BAFFLE BOX</b> |             |                 |                  |                     |
| <b>DESCRIPTION</b>  | <b>UNIT</b> | <b>QUANTITY</b> | <b>UNIT COST</b> | <b>TOTAL COST</b>   |
| Nutrient Separating Baffle Box - 48" Pipe   | EA          | 1               | 126000           | 126000              |
| Storm Pipe - 48" RCP  | LF          | 80              | \$ 230           | \$ 18,400           |
| Concrete weir - form and pour in place  | CY          | 104             | \$ 900           | \$ 93,600           |
| Regular Excavation  | CY          | 19360           | \$ 7             | \$ 135,520          |
| Subsoil Excavation  | CY          | 48,400          | \$ 6             | \$ 290,400          |
| Sod   | SY          | 13,300          | \$ 2             | \$ 26,600           |
| Silt Fence  | LF          | 3,800           | \$ 2             | \$ 7,600            |
| Floating Turbidity Barrier  | LF          | 300             | \$ 9             | \$ 2,700            |
| <b>Materials Subtotal</b>   |             |                 |                  | <b>\$ 700,820</b>   |
| Temporary Traffic Control (5%)  |             |                 |                  | \$ 35,041           |
| Staging Area (5%)   |             |                 |                  | \$ 35,041           |
| Mobilization (10%)  |             |                 |                  | \$ 70,082           |
| Contingency (30%)   |             |                 |                  | \$ 210,246          |
| <b>Construction Total</b>   |             |                 |                  | <b>\$ 1,051,230</b> |
| <b>Property Acquisition</b>   |             |                 |                  | <b>\$ 2,012,580</b> |
| <b>Design and Permitting</b>  |             |                 |                  | <b>\$ 90,000</b>    |
| <b>Annual Operations &amp; Maintenance Cost</b>   |             |                 |                  | <b>\$ 5,500</b>     |
| <b>CONCEPTUAL PLAN COST - DRY RETENTION AREA; NSBB</b>                                    |             |                 |                  | <b>\$ 3,159,310</b> |
| <b>CONCEPTUAL PLAN COST ESTIMATE - LINEAR TREATMENT AREA / FLOODPLAIN BENCH</b>           |             |                 |                  |                     |
| <b>DESCRIPTION</b>  | <b>UNIT</b> | <b>QUANTITY</b> | <b>UNIT COST</b> | <b>TOTAL COST</b>   |
| Storm Pipe - 18" RCP  | LF          | 120             | \$ 90            | \$ 10,800           |
| Storm Structure - MES - 18"   | EA          | 6               | \$ 1,810         | \$ 10,860           |
| Concrete weir - form and pour in place  | CY          | 22              | \$ 900           | \$ 19,800           |
| Regular Excavation  | CY          | 6,000           | \$ 7             | \$ 42,000           |
| Subsoil Excavation  | CY          | 45,000          | \$ 6             | \$ 270,000          |
| Sod   | SY          | 6,900           | \$ 2             | \$ 13,800           |
| Silt Fence  | LF          | 6600            | \$ 2             | \$ 13,200           |
| Floating Turbidity Barrier  | LF          | 2               | \$ 9             | \$ 18               |
| Wetland plantings   | AC          | 0.36            | \$ 6,000         | \$ 2,160            |
| <b>Materials Subtotal</b>   |             |                 |                  | <b>\$ 382,638</b>   |
| Temporary Traffic Control (5%)  |             |                 |                  | \$ 19,132           |
| Staging Area (5%)   |             |                 |                  | \$ 19,132           |
| Mobilization (10%)  |             |                 |                  | \$ 38,264           |
| Contingency (30%)   |             |                 |                  | \$ 114,791          |
| <b>Construction Total</b>   |             |                 |                  | <b>\$ 573,957</b>   |
| <b>Design and Permitting</b>  |             |                 |                  | <b>\$ 60,000</b>    |
| <b>Annual Operations &amp; Maintenance Cost</b>   |             |                 |                  | <b>\$ 2,000</b>     |
| <b>CONCEPTUAL PLAN COST - LINEAR TREATMENT AREA / FLOODPLAIN BENCH</b>                    |             |                 |                  | <b>\$ 635,957</b>   |
| Note: Percentages based on Materials Subtotal   |             |                 |                  |                     |



## US-41 and 10<sup>th</sup> Street – Coastal



### Project Management Area

A large part of the intensely urbanized downtown core drains directly into the bay at the 10<sup>th</sup> St. boat ramp. Largely untreated stormwater with a few BMPs is found in this area. There are flood LOS deficiencies in part of the roadways.

### Conceptual BMP

- A sediment sump (pink) will capture sediment and nutrients prior to discharge into the Bay.
- Existing open conveyance will be improved with low flow weirs and side-bank BAM filter
- LID retrofit of existing impervious parking area

**Score 80**

**Cost \$2,972,626**

### Benefits

- Annual TN Removal = 710 lb/yr
- \$209/lb TN over 20 year expected life of the three combined BMPs
- Resilient in NOAA 2100 future condition
- No feasible flood protection project was identified for this area due to lack of available land.

| PROJECT MANAGEMENT AREA: US 41 & 10TH STREET  |      |          |           |                     |
|---|------|----------|-----------|---------------------|
| CONCEPTUAL PLAN COST ESTIMATE - CONVERT EXISTING PARKING SPOTS TO PERVIOUS PAVEMENT |      |          |           |                     |
| DESCRIPTION   | UNIT | QUANTITY | UNIT COST | TOTAL COST          |
| Clearing and Grubbing   | AC   | 2        | \$ 18,800 | \$ 30,080           |
| Pervious Concrete - 6" layer  | SY   | 7744     | \$ 75     | \$ 580,800          |
| Bedding Stone   | TN   | 2,672    | \$ 130    | \$ 347,360          |
| Silt Fence  | LF   | 1,500    | \$ 2      | \$ 3,000            |
| Inlet Protection  | EA   | 18       | \$ 140    | \$ 2,520            |
| <b>Materials Subtotal</b>   |      |          |           | <b>\$ 963,760</b>   |
| Temporary Traffic Control (5%)  |      |          |           | \$ 48,188           |
| Staging Area (5%)   |      |          |           | \$ 48,188           |
| Mobilization (10%)  |      |          |           | \$ 96,376           |
| Contingency (30%)   |      |          |           | \$ 289,128          |
| <b>Construction Total</b>   |      |          |           | <b>\$ 1,445,640</b> |
| <b>Design and Permitting</b>  |      |          |           | <b>\$ 40,000</b>    |
| <b>Annual Operations &amp; Maintenance Cost</b>                                     |      |          |           | <b>\$ 2,500</b>     |
| CONCEPTUAL PLAN COST  |      |          |           | <b>\$ 1,488,140</b> |
| CONCEPTUAL PLAN COST ESTIMATE - LOW FLOW WEIRS WITH SIDE-BANK FILTRATION            |      |          |           |                     |
| DESCRIPTION   | UNIT | QUANTITY | UNIT COST | TOTAL COST          |
| Regular Excavation  | CY   | 1,620    | \$ 7      | \$ 11,340           |
| Embankment  | CY   | 310      | \$ 9      | \$ 2,790            |
| Underdrain-6"   | LF   | 2,080    | \$ 90     | \$ 187,200          |
| Bedding Stone   | TN   | 310      | \$ 130    | \$ 40,300           |
| Biosorption Activated Media   | CY   | 1000     | \$ 200    | \$ 200,000          |
| Concrete weir - form and pour in place  | CY   | 20       | \$ 900    | \$ 18,000           |
| Rip Rap   | TN   | 43       | \$ 120    | \$ 5,186            |
| Sod   | SY   | 1850     | \$ 2      | \$ 3,700            |
| Silt Fence  | LF   | 2,400    | \$ 2      | \$ 4,800            |
| Floating Turbidity Barrier  | LF   | 120      | \$ 9      | \$ 1,080            |
| <b>Materials Subtotal</b>   |      |          |           | <b>\$ 463,056</b>   |
| Temporary Traffic Control (5%)  |      |          |           | \$ 23,153           |
| Staging Area (5%)   |      |          |           | \$ 23,153           |
| Mobilization (10%)  |      |          |           | \$ 46,306           |
| Contingency (30%)   |      |          |           | \$ 138,917          |
| <b>Construction Total</b>   |      |          |           | <b>\$ 694,584</b>   |
| <b>Design and Permitting</b>  |      |          |           | <b>\$ 55,000</b>    |
| <b>Annual Operations &amp; Maintenance Cost</b>                                     |      |          |           | <b>\$ 2,500</b>     |
| CONCEPTUAL PLAN COST  |      |          |           | <b>\$ 1,215,140</b> |
| CONCEPTUAL PLAN COST ESTIMATE - SEDIMENT SUMP                                       |      |          |           |                     |
| DESCRIPTION   | UNIT | QUANTITY | UNIT COST | TOTAL COST          |
| Sheet Pile  | LF   | 194      | \$ 800    | \$ 155,200          |
| Rip-Rap   | TN   | 16       | \$ 120    | \$ 1,920            |
| Subsoil Excavation  | CY   | 767      | \$ 6      | \$ 4,602            |
| floating turbidity barrier  | LF   | 500      | \$ 9      | \$ 4,500            |
| <b>Materials Subtotal</b>   |      |          |           | <b>\$ 166,222</b>   |
| Temporary Traffic Control (5%)  |      |          |           | \$ 3,324            |
| Staging Area (5%)   |      |          |           | \$ 8,311            |
| Mobilization (10%)  |      |          |           | \$ 16,622           |
| Contingency (30%)   |      |          |           | \$ 49,867           |
| <b>Construction Total</b>   |      |          |           | <b>\$ 244,346</b>   |
| <b>Design and Permitting</b>  |      |          |           | <b>\$ 30,000</b>    |
| <b>Annual Operations &amp; Maintenance Cost</b>                                     |      |          |           | <b>\$ 1,750</b>     |
| CONCEPTUAL PLAN COST  |      |          |           | <b>\$ 276,096</b>   |
| Note: Percentages based on Materials Subtotal                                       |      |          |           |                     |



Enter a Census Tract number into the search. From the Search Results drop panel, select the Tract and Block number combination as input to the Income Summary tool. The tool will then summarize the LOM Income percentages for the selected and adjacent blocks.

0 Feet



2020 Census Block Group 5


LMI % 74.57

2015 Census Block Group 5

LMI % 75.47

### Layers

- > County Infrastructure Layers
- > Census Block Group Layers
- > ACS Variable Layers
- > County Boundary Layers





Enter a Census Tract number into the search. From the Search Results drop panel, select the Tract and Block number combination as input to the Income Summary tool. The tool will then summarize the LOM Income percentages for the selected and adjacent blocks.

0 Feet

+

-

St

Search by Tract Number or Address

2020 Census Block Group 4


LMI % 70.64

2015 Census Block Group 4

LMI % 64.5

Layers

- County Infrastructure Layers
- Census Block Group Layers
- ACS Variable Layers
- County Boundary Layers





Enter a Census Tract number into the search. From the Search Results drop panel, select the Tract and Block number combination as input to the Income Summary tool. The tool will then summarize the LOM Income percentages for the selected and adjacent blocks.

0 Feet



2020 Census Block Group 4


LMI % 55.86

2015 Census Block Group 4

LMI % 47.08

Layers

- > County Infrastructure Layers
- > Census Block Group Layers
- > ACS Variable Layers
- > County Boundary Layers





### Tri-Par Area

The Tri-Par Area is subject to historic flooding, located within Whitaker Bayou basin at the confluence of Whitaker Main Canal and Tributary A, as well as confluence of Tributaries A and B. The area has a history of flooding and includes significant nitrogen loading as well – which is primarily due to the age and intensity of land-use and commercial/industrial land-use types.




Figure 21 - Tri-Par Priority Management Area



### 17th and US-301 Area

This area has street flooding level of service deficiencies on US - 301, existing street flooding on US - 301, 17th Street and N. East Ave and Structure flooding LOS deficient for 10 commercial buildings. The area also experiences high or medium nitrogen loading throughout.




Figure 25 - 17th & US301 Priority Management Area



### US-41 and 10<sup>th</sup> Street Area

There is a roadway LOS deficiency on US-41 with high or medium nutrient loading. Intense urban development upstream of the 10th Street boat basin contributes to the direct discharge of stormwater run-off into Sarasota Bay. The boat basin has been maintained throughout the years and a sediment removal project was completed in 2018. SWFWMD cooperatively funded project No. W606 to install a nutrient separating baffle box on 10<sup>th</sup> St. just east of Florida Ave. The Bay Partnership is redeveloping the City owned bayfront into a more highly used public space and is interested in partnering on improvements.




Figure 26 - US 41 & 10th Street Priority Management Area